

MATERIAL SAFETY DATA SHEET

MSDS Name: THURMALOX BLACK  
MSDS Number: 290  
Version Number  
MSDS Date: JAN-31-2005  
Page Number: 1

SECTION 1. PRODUCT AND COMPANY INFORMATION

Product Name: THURMALOX BLACK  
CAS Number: N/A  
Hazard Rating: Health: 2 Fire: 3 Reactivity: 0 PPI:

Company Identification: DAMPNEY CO INC.  
85 PARIS ST  
EVERETT MA 02149-4411

Contact: PETER BARRETT  
Telephone/Fax: (617) 389-2805 (617) 389-0484  
Emergency Phone (24 Hour): EVENING ADMINISTRATOR  
(800) 424-9300  
Chemtrec (24 Hour): (800) 424-9300

Product Class: SILICONE COATING  
Trade Name: THURMALOX BLACK  
Product Code: 290

SECTION 2. INGREDIENT AND HAZARD INFORMATION

Ingredient Name	CAS Number	Percent	TSCA
TOLUENE (HAPS)	108-88-3	41.89	Y
XYLENE (HAPS)	1330-20-7	21.40	Y
BUTANOL	71-36-3	2.38	Y
MANGANESE COMPOUNDS	N/A	1.97	Y
ETHYL BENZENE (HAPS)	100-41-4	1.48	Y

\*\*\* ALL Ingredients in this product are listed in the T.S.C.A. Inventory

\*\* SPECIAL REMARKS ON ABOVE LISTED INGREDIENTS \*\*

Technical grade xylene contains 18-20% ethyl benzene CAS # is 100-41-4 and is subject to reporting requirements of SECTION 313 of SARA TITLE III.

ACGIH recommends a TWA of 50 ppm for toluene (skin).

MATERIAL SAFETY DATA SHEET

MSDS Name: THURMALOX BLACK  
MSDS Number: 290  
Version Number  
MSDS Date: JAN-31-2005  
Page Number: 2

---

---

SECTION 3. PHYSICAL DATA

---

pH Value: Not Applicable  
Boiling Range: 230.(F - 286.(F  
Melting Point: Not Applicable  
Evaporation Rate: 0.641 times Faster than n-Butyl Acetate  
  
Vapor Density: Heavier than air  
  
Partition Coefficient Not Available  
% Volatile Weight 67.4%  
% Volatile 82.1%  
Specific Gravity: 1.055  
Weight/Gallon: 8.78 lbs  
VOC 5.94 LBS/GAL  
Heavy Elements (ppm) 0.

---

---

SECTION 4. FIRE AND EXPLOSION HAZARD DATA

---

Flammability Class 1B  
Flash Range: 45.(F - 97.(F  
Explosive Range: 1.%  
11.2%

EXTINGUISHING MEDIA:

Foam, alcohol foam, CO<sub>2</sub>, dry chemical, water fog may be ineffective but should be used to cool fire-exposed containers to prevent pressure build up and possible auto-ignition or explosion when exposed to extreme heat.

SPECIAL FIREFIGHTING PROCEDURES:

Use full protection equipment including self contained breathing apparatus (NIOSH approved) for respiratory protection in fighting fires in enclosed or confined spaces, or as otherwise needed. Minimize breathing gases, vapors, fumes or decomposition products.

UNUSUAL FIRE & EXPLOSION HAZARDS:

During emergency conditions, overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

MATERIAL SAFETY DATA SHEET

MSDS Name: THURMALOX BLACK  
MSDS Number: 290  
Version Number  
MSDS Date: JAN-31-2005  
Page Number: 3

SECTION 5. HEALTH HAZARD DATA

Route	Species	Exposure and Dose
TOLUENE (HAPS)		
Inhalation	Unknown	LD50 8000. PPM
Oral	Unknown	LD50 5. PPM
Skin	Unknown	LD50 14. PPM
BUTANOL		
Inhalation	Unknown	LD50 8000. PPM
Oral	Unknown	LD50 790. PPM
Skin	Unknown	LD50 4.2 PPM

PERMISSIBLE EXPOSURE LEVEL:  
SEE SECTION VIII

EFFECTS OF OVEREXPOSURE:

Primary route(s) of entry:

(X) Dermal (X) Inhalation ( ) Ingestion

Acute (short term) exposure:

Inhalation - excessive inhalation of vapors can cause nasal and respiratory irritation, cns effects including dizziness, weakness, nausea, headache, possible unconsciousness, and even death.

Skin contact - prolonged or repeated contact can cause moderate irritation, defatting, and dermatitis.

Eye contact - can cause severe irritation, redness, tearing, and blurred vision.

Ingestion - can cause gastrointestinal irritation, nausea, vomiting, and diarrhea. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal.

Damage to humans: chronic overexposure of Butanol may aggravate pre-existing disorders, affect the hearing, anemia. Overexposure to Butanol has been found to cause the following effects in laboratory animals: anemia, liver abnormalities, kidney damage, eye and lung damage.

Butanol has been shown to cause harm to the fetus in laboratory animal studies. Harm to the fetus occurs only at exposure levels that harm the pregnant animal. the relevance of the findings to humans is uncertain.

EMERGENCY AND FIRST AID PROCEDURES:

Eyes - flush thoroughly with running water for 15 minutes, including under eyelids. Get medical attention.

Continued

MATERIAL SAFETY DATA SHEET

MSDS Name: THURMALOX BLACK  
MSDS Number: 290  
Version Number  
MSDS Date: JAN-31-2005  
Page Number: 4

---

---

SECTION 5. HEALTH HAZARD DATA

Continued

Skin - promptly remove contaminated clothing and wash affected areas thoroughly with soap and water. If irritation occurs get medical attention. Wash contaminated clothing thoroughly before re-use.

Inhalation - if overcome by vapor, remove to an area free from risk of further exposure. If breathing is difficult, administer oxygen, or artificial respiration if breathing has stopped. Keep person warm and quiet and get medical attention.

Ingestion - if swallowed, call a physician immediately. Only induce vomiting at the instructions of a physician. Never give anything by mouth to an unconscious person. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE:

Pre-existing eye, skin, liver and/or kidney disorders may be aggravated by exposure to this product.

Chronic (long term) exposure:

In laboratory animals - overexposure to this material (or its components) has been found to cause the following effects; anemia, liver abnormalities, kidney, lung and spleen damage.

In humans - liver and cardiac abnormalities.

Toluene may be harmful to the fetus based on laboratory animal studies. Repeated exposure to toluene has been associated with high frequency hearing loss based on evidence in laboratory animals. The human health consequences of this finding is uncertain.

Chronic overexposure to xylene has been suggested to cause cardiac abnormality in humans.

---

---

SECTION 6. STABILITY AND REACTIVITY MEASURES

Stability: This product is stable  
Hazardous Polymerization: Hazardous polymerization will not occur

INCOMPATIBILITY:

Avoid contact with strong oxidizing agents, acids or bases.

CONDITIONS TO AVOID:

Avoid heat, open flames.

HAZARDOUS DECOMPOSITION PRODUCTS:

Carbon monoxide and unidentified organics may be formed.

MATERIAL SAFETY DATA SHEET

MSDS Name: THURMALOX BLACK  
MSDS Number: 290  
Version Number  
MSDS Date: JAN-31-2005  
Page Number: 5

SECTION 7. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Before attempting cleanup, refer to hazard caution information in other sections of this sheet. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Large spills - notify safety personnel. Eliminate potential sources of ignition. Wear appropriate respirator and protective clothing. Soak up with an absorbent, I.E. sand, clay, or other suitable material. Place in non-leaking containers and seal tightly for proper disposal. Ventilate confined spaces. Minimize breathing vapors. Open all windows and doors. Minimize skin contact. Keep product out of sewers and water courses by diking and impounding. Observe precautions for volatile, combustible vapors from absorbed material.

Small spills - take up with absorbent material and place in non-leaking containers for proper disposal.

WASTE DISPOSAL METHOD:

Assure conformity with applicable federal, state and local regulations.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

	ACGIH TLV	ACGIH TLV-C	ACGIH STEL	OSHA STEL	OSHA PEL
TOLUENE (HAPS)	50.00 PPM	N/est	100.00 PPM	100.00 PPM	100.00 PPM
XYLENE (HAPS)	100.00 PPM	N/est	150.00 PPM	150.00 PPM	100.00 PPM
BUTANOL	50.00 PPM	N/est	N/est	N/est	50.00 PPM
MANGANESE COMPOUNDS	0.20 mg/M3	N/est	5.00 mg/M3	N/est	5.00 mg/M3
ETHYL BENZENE (HAPS)	100.00 PPM	N/est	125.00 PPM	125.00 PPM	100.00 PPM

RESPIRATORY PROTECTION:

Use NIOSH approved respirator as required to prevent overexposure.

Continued

MATERIAL SAFETY DATA SHEET

MSDS Name: THURMALOX BLACK  
MSDS Number: 290  
Version Number  
MSDS Date: JAN-31-2005  
Page Number: 6

---

---

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Continued

---

Unconfined spaces - use a vapor/particulate respirator such as  
NIOSH approved No. TC-23C.  
Confined spaces - use a constant flow air-line respirator such as  
NIOSH approved NO. TC-19C.

VENTILATION:

Traces of Benzene and Formaldehyde may form when this product is  
heated above 300 degrees F. Evolution rate is highest during the  
first few hours, then subsequently approaches zero. Personnel  
should wear organic vapor respirators until workplace exposure  
levels have been determined. Review the OSHA Benzene regulations  
for detailed information on safe handling requirements.

OSHA PEL for Formaldehyde is 0.75 ppm.

OSHA PEL for Benzene is 10 ppm.

Provide sufficient ventilation to keep air contaminant  
concentration below current applicable OSHA permissible exposure  
limit or ACGIH's TLV limit.

No smoking or open lights.

PROTECTIVE GLOVES:

Use chemical-resistant gloves to prevent skin contact.

EYE PROTECTION:

Use chemical splash goggles or face shield to prevent eye  
contact.

OTHER PROTECTIVE EQUIPMENT:

Use chemical-resistant or other protective outerwear to protect  
against clothing contamination and skin contact.

---

---

SECTION 9. SPECIAL PRECAUTIONS

---

PRECAUTIONS TO BE TAKEN IN HANDLING, TRANSPORTATION, AND STORING:

CAUTION! FLAMMABLE! Handling and storage conditions must be  
suitable for OSHA CLASS I flammable liquid. Store in cool,  
well-ventilated, fire resistant storage area. Protect containers  
against physical damage. Keep away from heat, flame, and strong  
oxidizing agents. Do not store above 100 degrees F. Use only  
with adequate ventilation. Keep containers closed when not in  
use. Do not breathe vapor or mist. Avoid contact with eyes,  
skin and clothing. Do not take internally. Bond and ground  
containers of this material when pouring to avoid static sparks  
which create a fire hazard.

OTHER PRECAUTIONS:

Contact lenses pose a special hazard; soft lenses may absorb and  
all lenses concentrate irritants.

MATERIAL SAFETY DATA SHEET

MSDS Name: THURMALOX BLACK  
MSDS Number: 290  
Version Number  
MSDS Date: JAN-31-2005  
Page Number: 7

SECTION 10. REGULATORY INFORMATION

SARA TITLE III SECTION 313:

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right to Know Act of 1986 and of 40 CFR 372:

Ingredient Name	CAS Number	Percent
TOLUENE (HAPS)	108-88-3	41.89
XYLENE (HAPS)	1330-20-7	21.40
BUTANOL	71-36-3	2.38
MANGANESE COMPOUNDS	N/A	1.97
ETHYL BENZENE (HAPS)	100-41-4	1.48

-PROP 65 (CARCINOGEN)

WARNING: this product contains a chemical known to the state of California to cause cancer.

Ingredient Name	CAS Number	Percent
TOLUENE (HAPS)	108-88-3	41.89
XYLENE (HAPS)	1330-20-7	21.40
ETHYL BENZENE (HAPS)	100-41-4	1.48
CRYSTALLINE SILICA	14808-60-7	0.06

The information and recommendation contained herein are based on data believed to be correct. However, Dampney makes no warranty expressed or implied regarding the accuracy of these data or results to be obtained from the use thereof. Dampney assumes no responsibility for personal injury or property damage caused by use of the material described herein. It is the responsibility of the purchaser or user to ensure that this material is properly and safely used.